

# LMC4 SERIES Upright Microscope



Version 2.0

**Brochure** 

### LMC-4000 SERIES

#### FOR CLINICAL AND RESEARCH



#### **KEY FEATURES**

- Y-Shaped body for maximum stability
   Carrying handle
- Stable main body
- Brightfield, Darkfield, Polarization, Metallurgical, Phase Contrast, & Fluorescence Contrast Methods
- · High contrast, broad beam optical design
- Modular design allows for flexibility in system configuration 100% customizable for every need

- Corrected for eyeglasses
- Carrying Handle
- LED Illumination
- Rackless Stage

#### **OPTICAL SYSTEM**

- · Infinity corrected optical system
- Plan Achromat objectives standard, Plan Fluor (optional)
- Wide range of magnifications: 2X, 4x, 10x, 20x, 40x, 60x & 100x
- Anti-reflective coatings on optics
- Sharp images with bright natural color
- · Parcentric and parfocal objectives

#### TRINOCULAR OPTICS

- 10x Eyepieces with 22mm widefield eyepieces
- 50 to 75mm interpupillary distance
- Light splitting ratio 0:100/50:50 (0:100/100:0 on FL models)
- Rubber eyecups
- Diopter adjustment
- Tilting Ergonomic head and standard fixed eyepiece configurations available

#### **STAND**

- Large, sturdy base designed for the lab environment
- Rack and pinion focusing mechanism for smooth focus control
- Rackless, X/Y mechanical stage with adjustable tension
- Built-in carrying handle for easy transportation of microscope
- · Coarse and fine focus adjustment
- · Reversed quintuple nosepiece
- Full Koehler illumination with field and iris diaphragm

### MULTI-OBSERVATION CONFIGURATIONS

- LED Pointer
- 12V/100W Illumination
- Supports up to 5 heads



	CAT. NO.	HEAD	OBJECTIVES	OPTICS	rov	F-CONTROLS	KOE- HLER	CONDENSER	ILLUM	STAGE	CEJ TURRET
	LMC48F1	BINOC	4X, 10X, 40X, 100X or	INFINITY, PL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	SWILED	RACKLESS X/Y MECH STAGE	S POS
9	LMC48F7	ERGO BINOC	2X, 4K, 10X, 40X, 100 K or	INFINITY, PL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	SWLED	RACKLESS X/Y MECH STAGE	5 POS
CHIME	LMC4PA1	TILTING ERGO TRINGC	2%, 4K, 10X, 40X, 100K or	PAFINITY, PL FLUOR	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	SWILED	RACKLESS X/Y MECH STAGE	45705
100	LMC4PA2	TILTING ERGO TRINGC	2X, 4K, 10X, 40X, 100 K or	INFINITY, PL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	SWLED	RACKLESS X/Y MECH STAGE	5 POS
	LMC4HVI3	TRINOC	4X, 10X, 40X, 50X ox, 100K ox	INFINITY, PL	22MW	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	5W LED	RACKLESS X/Y MECH STAGE	5 POS
COUT	LMC4GT4	TRINOC	4X, 10X, 40X, 50X cs, 100X cs	INFINITY, PL	22MW	COARSE & FINE	FULL	11.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A GOUT KIT	SWLED	RACKLESS X/Y MECH STAGE	S POS
P	LMC4DF3	TRINOC	2X, 4X, 10X, 20X, 40X	INFINITY, PL	22MM	COARSE & FINE	FULL	1.25 N.A. ABBE, DARKFIELD OF UP TO 40X	SWILED	RACKLESS X/Y MECH STAGE	5 POS
Darké	LMC4DF4	TRINOC	4X, 10X, 20X, 40X, 100X or	INFINITY, PL	22MM	COARSE & FINE	FULL	1.25 N.A. ABBE, DARKFIELD OF UP TO 100X	5W LED	RACKLESS X/Y MECH STAGE	5 POS
PHASE	LMC4PH18	TRINOC	4X BF, 1007H, 200FH, 400FH, 100XFH or	INFINITY, PL PH	22MM	COARSE & FINE	FULL	1.25 N.A. ABBE, 5-POSITION PHASE CONTRAST TURRET	5W LED	RACKLESS X/Y MECH STAGE	5 POS
PHASS/FOL	LMC4-AB3	TRINDC	4X BF, 10XPH, 2XXPH, 40XPH	INFINITY, PL PH	22MM	COARSE & FINE	PULL	1.25 N.A. ABBE, 5-POSITION PHASE CONTRAST TURRET	SWILED	RACKLESS X/Y MECH STAGE	5 PO6
2 HEAD	LMC4MD2	TRINOC (MAIN) BINOC (OBSERVER)	28, 48, 10X, 40X, 100K or	IMPINITY, PL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	12W/100W HAL	RACKLESS X/Y MECH STAGE	5 PO6
SHEAD	LMC4WD3	TRINOC (MAIN) BINOC (OBSERVER)	28, 4K, 10X, 40X, 100K ca	IMPINITY, PL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	12V/100W HAL	RACKLESS X/Y MECH STAGE	5 PO6

# LMC-4000 SERIES FLUORESCENCE

















#### **KEY FEATURES**

- · Y-Shaped body for maximum stability
- Carrying handle
- Stable main body
- Brightfield, Darkfield, Polarization, Metallurgical, Phase Contrast, & Fluorescence Contrast Methods
- · High contrast, broad beam optical design
- Modular design allows for flexibility in system configuration
- 100% customizable for every need

#### **OPTICAL SYSTEM**

- Infinity corrected optical system
- Plan Achromat objectives standard, Plan Fluor (optional)
- Wide range of magnifications: 2X, 4x, 10x, 20x, 40x, 60x & 100x
- · Anti-reflective coatings on optics
- · Sharp images with bright natural color
- Parcentric and parfocal objectives

#### LED FLUORESCENCE

- · 25,000 hour life span
- · No alignment needed
- · LED wave length specific to filter set
- · Adjustable light intensity
- · High signal to noise ratio
- Stable light excitation energy
- No warm-up or cool down time
- Produces no harmful UV light
- · Powered by optional battery pack











#### MERCURY FLUORESCENCE

- Full spectrum illumination
- · 100 watt mercury bulb
- Digital power supply
- Centerable lamp housing
- 6 position fluorescence turret
- · Brightfield and fluorescence observation
- · Fluorescence light block



	CAT. NO.	HEAD	OBJECTIVES	OPTICS	FOV	F-CONTROLS	KOE- HLER	CONDENSER	ILLUM	STAGE	OBJ TURRET	GFP FILTER	RFP FILTER	DAPI FILTER
LEDFL	LMC4FL4	TRINOC	4X, 10X, 20X, 40X, 100X oil	INFINITY, PL FLUOR	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	5W LED	RACKLESS X/Y MECH STAGE	5 POS		2560 +/- 20 2645 +/- 37	0865 +/- 25 0460 +/- 25
MERCURY FL	LMC4FL2	TRINOC	4X, 10X, 20X, 40X, 100X oil	INFINITY, PL FLUOR	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	5W LED	RACKLESS X/Y MECH STAGE	5 POS	470 +/- 20 20 525 +/- 20	560 +/- 20 645 +/- 37	1365 +/- 25 1460 +/- 25

## LMC-4000 SERIES

#### **POLARIZATION**











Stage Locking

Stress Free Objectives

50W Halogen

#### **KEY FEATURES**

- Y-Shaped body for maximum stability-Carrying handle
- Can be purchased pre-configured or customized for your specific requirements
- High contrast, broad beam optical design
- Modular Transmitted and reflected light polarization for identification of crystallized structures in biological or material samples
- Can be purchased pre-configured or customized for your specific requirements
- Anti-corrosive and friction coated, graphite stage
- Intermediate device for conoscopic observation with internal Bertrand lens, Analyzer, Compensator, and Wave Plates. Easily determine the degree of polarization for crystal identification.

**OPTICAL SYSTEM** 

- Infinity corrected optical system
- Plan POL and LMPlan POL objectives available
- Wide range of magnifications: 4x, 5x, 10x, 20x, 40x, 60x & 100x
- Central stop dispersion staining objectives available for asbestos analysis
- Sharp images with bright natural color
- Parcentric and parfocal objectives

#### **STAND**

- Large, sturdy base designed for the lab environment
- Rack and pinion focusing mechanism for smooth focus control
- Rotating Stage with Stage Lock
- · Coarse and fine focus adjustment
- · Centerable objective nosepiece
- Full Koehler illumination with field and iris diaphragm





Bayonet locking mechanism on eyepiece ensures that the reticle remains orthogonal with the polarizer and analyzer.

Intermediate device for conoscopic observation with internal Bertrand lens, Analyzer, Compensator, and Wave Plates. Easily determine the degree of polarization for crystal identification.





50 Watt reflected light illuminator allows for viewing transmitted or reflected light. A pre-centered bulb ensure easy replacement of the bulb.

CAT. NO.	HEAD	OBJECTIVES	OPTICS	FOV	F-CONTROLS	KOEHLER	CONDENSER	ILLUM	STAGE	OBJTURRET
LMC4PL5	TRINOC	4X, 10X, 20X, 60X	INFINITY, STRAIN FREE PL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	TRANSMITTED 50W HAL	ROUND, ROTATING	4 POS CENTERABLE
LMC4PL6	TRINOC	5X, 10X, 20X, 50X	INFINITY, STRAIN FREE LMPL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	TRANSMITTED AND REFLECTED 50W HAL	ROUND, ROTATING	4 POS, CENTER- ABLE
LMC4-AB2	TRINOC	4X, 10X (CS), 20X, 40X (CS)	INFINITY STRAIN FREE, CENTRAL STOP (10X & 40X)	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	TRANSMITTED 50W HAL	ROUND, ROTATING	4 POS CENTERABLE

# LMC-4000 SERIES METALLURGICAL

















#### **KEY FEATURES**

- · Y-Shaped body for maximum stability
- · Carrying handle
- Ultra-Bright LED Illumination, reflected and transmitted light for Material Science applications
- Reflected and transmitted light for Material Science applications
- Can be purchased separately or in a pre-configured system

#### **OPTICAL SYSTEM**

- · Infinity corrected optical system
- LMPlan objectives
- Wide range of magnifications: 5x, 10x, 20x, 50x & 100x
- · Sharp images with bright natural color
- · Parcentric and parfocal objectives

SERIES	MAGNIFICATION	N.A.	W.D.	F.N.	COVER GLASS THICKNESS	IMMERSION
	5 X	0.15	10.80	22	-	/
	10X	0.30	10.00	22	-	/
LMPLAN	20X	0.45	4.00	22	-	/
	50X	0.55	7.90	22	-	/
	100X	0.80	2.10	22	-	/





#### **STAND**

- Large, sturdy base designed for the lab environment
- Rack and pinion focusing mechanism for smooth focus control
- Adjustable stage height. 28mm sample height in transmitted and 78mm high samples in reflected light allows for maximum flexibility on the times of materials
- · that can be viewed on this system
- · Coarse and fine focus adjustment
- Full Koehler illumination with field and iris diaphragm







5 Watt reflected light illuminator with field and iris diaphragm, polarization and color filter options.

Both transmitted and reflected light options with independent light intensity control.



CAT. NO.	HEAD	OBJECTIVES	OPTICS	FOV	F-CONTROLS	KOEHLER	CONDENSER	ILLUM	STAGE	OBJTURRET
LMC4MT5	TRINOC	5X, 10X, 20X, 50X	INFINITY, PLAN LWD METL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	TRANSMITTED AND REFLECTED 5W LED	RACKLESS X/Y MECH STAGE	5 POS
LMC4MT7	TRINOC	5X, 10X, 20X, 50X, 100x	INFINITY, PLAN LWD METL	22MM	COARSE & FINE	FULL	1.2 N.A. ABBE, WITH IRIS AND FLIP OUT LENS WITH 0.9 N.A.	TRANSMITTED AND REFLECTED 5W LED	RACKLESS X/Y MECH STAGE	5 POS



LAXCO, Inc. 18303 Bothell-Everett Hwy Suite 140 Mill Creek, WA 98012 sales@laxco.com www.laxcoinc.com

Contact us: For customer service: 425-686-3081 For service support: 425-686-3081 For technical support: 425-686-3081

LMC-MKT-DOC-1700111(2)